



136 South Maple Ave 970-249-7922 p
 Montrose, CO 81401 970-240-6988 f

RECLA METALS L.L.P.

Toll Free 1-888-621-0807

www.reclametals.com

SS 7/8" Profile

Panel	Corrugated 2.67 X 7/8"								
Live Load		20 PSF		30 PSF		40 PSF		50 PSF	
	Span	Roof	Wall	Roof	Wall	Roof	Wall	Roof	Wall
24g 142 lbs/sq	1	7'2"	8'3"	5'11"	6'9"	5'2"	5'10"	4'8"	5'3"
	2	7'2"	8'3"	5'11"	6'9"	5'2"	5'10"	4'8"	5'3"
	3	8'0"	9'3"	6'8"	7'7"	5'9"	6'6"	5'2"	5'10"
22g 172 lbs/sq	1	7'11"	9'-2"	6'-7"	7'-6"	5'-9"	6'-6"	5'-2"	5'-10"
	2	7'11"	9'-3"	6'-7"	7'-6"	5'-9"	6'-6"	5'-2"	5'-10"
	3	8'11"	10'-4"	7'-4"	8'-5"	6'-5"	7'-3"	5'-9"	6'-6"

Notes:

- * Roof loads are for positive loads only and are in addition to weight of panel.
- * Siding loads are for positive or negative loading.
- * Maximum allowable stress for Grade A (F) = 20,000 PSI for roofs and 26,667 PSI for walls where wind is only load.
- * Loads and spans for carbon steel are based on AISI Cold Formed Steel Design Manual.