



136 South Maple Ave 970-249-7922 p
 Montrose, CO 81401 970-240-6988 f

ECLA METALS L.L.P

Toll Free 1-888-621-0807

www.reclametals.com

SS 1/2" Profile

Panel	Corrugated 2.67 X 1/2"								
Live Load		20 PSF		30 PSF		40 PSF		50 PSF	
	Span	Roof	Wall	Roof	Wall	Roof	Wall	Roof	Wall
24g 124 lbs/sq	1	4'8"	5'5"	4'0"	4'6"	3'5"	3'11"	3'1"	3'6"
	2	4'10"	5'6"	4'0"	4'6"	3'5"	3'11"	3'1"	3'6"
	3	5'5"	6'2"	4'5"	5'0"	3'10"	4'4"	3'6"	3'11"
22g 151 lbs/sq	1	5'1"	5'10"	4'5"	5'0"	3'10"	4'4"	3'5"	3'10"
	2	5'4"	6'1"	4'5"	5'0"	3'10"	4'4"	3'5"	3'10"
	3	5'10"	6'10"	4'11"	5'7"	4'3"	4'10"	3'10"	4'4"

Notes:

- * Roof loads are for positive loads only and are in addition to weight of panel.
- * Siding loads are for positive or negative loading.
- * Maximum allowable stress for Grade A (F) = 20,000 PSI for roofs and 26,667 PSI for walls where wind is only load.
- * Loads and spans for carbon steel are based on AISI Cold Formed Steel Design Manual.