

Understanding Superior Service



PVDF COLOR SELECTION

| | | | |
|---|---|---|--|
|  |  |  |  |
| REGAL WHITE SR .68 SRI 82 | SNOW WHITE SR .63 SRI 75 | ALMOND SR .60 SRI 70 | SANDSTONE SR .54 SRI 63 |
|  |  |  |  |
| ASH GRAY SR .39 SRI 41 | TUNDRA SR .34 SRI 35 | SLATE GRAY SR .42 SRI 47 | CHARCOAL SR .32 SRI 32 |
|  |  |  |  |
| BROWNSTONE SR .38 SRI 40 | SURREY BEIGE SR .40 SRI 43 | COLONIAL RED SR .33 SRI 34 | REGAL RED SR .42 SRI 45 |
|  |  |  |  |
| MEDIUM BRONZE SR .30 SRI 31 | DARK BRONZE SR .26 SRI 24 | PATRICIAN BRONZE SR .27 SRI 26 | MANSARD BROWN SR .30 SRI 30 |
|  |  |  |  |
| PATINA GREEN SR .46 SRI 51 | EVERGREEN SR .26 SRI 24 | CLASSIC GREEN SR .28 SRI 27 | MATTE BLACK SR .27 SRI 26 |
|  |  |  |  |
| ROMAN BLUE SR .26 SRI 24 | REGAL BLUE SR .26 SRI 24 | BRANDYWINE SR .26 SRI 24 | COPPER METALLIC SR .45 SRI 50 |
|  |  |  | |
| PRE-WEATHER GALVALUME SR .30 SRI 27 | SILVER METALLIC SR .58 SRI 66 | CHAMPAGNE SR .38 SRI 38 | |

- Final color selection should be made from actual color chips.
- Visit www.unitedsteelsupply.com for the most current information.
- A 40-year limited paint warranty is available for all colors upon written request. Please inquire. (Outside the continental United States, please inquire.)
- Solar Reflectivity (SR): Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance. ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit www.energystar.gov.
- Solar Reflectance Index (SRI): The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit www.usgbc.org.

UNITED STEEL SUPPLY

Standard Color OFFERINGS

PROUDLY FINISHED WITH
SHERWIN-WILLIAMS
Coil Coatings

